



CIRCUITS	DIM. A	DIM. B
2	1.25	7.7
3	2.50	8.9
4	3.75	10.2
5	5.00	11.4
6	6.25	12.7
7	7.50	13.9
8	8.75	15.2
9	10.00	16.4
10	11.25	17.7
11	12.50	18.6
12	13.75	20.2
13	15.00	21.4
14	16.25	22.7
15	17.50	23.9

**NOTES**

- \* Poles:2~15
  - \* Insulator:high temperature plastic UL94V-0  
HTN6T UL94V-0
  - \* Contact:phosphor bronze Matte Tin-plated
  - \* Tab:Brass Matte Tin plated
  - \* Mates with CH1251-XX series housing
- Specifications**
- \* Current rating: 1A AC, DC
  - \* Voltage rating: 125V AC, DC
  - \* Temperature range: -40°C~+85°C
  - \* Insulation resistance: 100MΩ min.
  - \* Withstand voltage: 250 AC/minute

**ORDERING CODE**

HW1252 ST - XX M - C - R  
 ① ② ③ ④ ⑤ ⑥

- ① SERIES NO.
- ② TERMINAT TYPE  
ST=180° SMT
- ③ NO. OF CIRCUIT
- ④ CONTACT PLATED  
M=MATTE TIN PLATED
- ⑤ CAP OPTION  
C=W/CAP  
N=W/O CAP
- ⑥ PACKING OPTION  
T: TUBE  
R: TAPE REEL

詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD.	TITLE	1.25mm pitch sraight angle SMT type	GENERAL TOLERANCE	DRAWN	DATE	2015.10.25		
	PART NO.	HW1252ST-XXM-C-R	DIM: X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	CHECK	DATE			
	DWG.NO.	HW1252ST-XXM-C-R		APPROVE	DATE			
				SCALE	UNIT	mm	REV.	01