



RECOMMEND P.C.B. LAYOUT
TOP VIEW

***Specification:**

- 1.Housing: Thermoplastic UL 94V-0, Color: Black;
- 2.Contact: Phosphor Bronze;
- 3.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin/Lead Plating on Solder Tail
- 4.Current Rating: 0.5 AMP. Max.;
- 5.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 6.Insulation Resistance: 1000 M Ohms Min. AT DC 500V
- 7.Contact Resistance: 50 M Ohms Max.;
- 8.Operating Temperature: -25°C to +85°C;
- 9.Processing Temp: 260°C for 15 Seconds Max.;

ORDER INFORMATION

SIM40-06 SA 0 R
1 2 3 4 5

1. SERIES NO
2. NO. OF POS
3. CONTACT PLATED
SA=SELECTIVE GOLD FLASH
4. POST OPTION
0=W/O LOCATING PEG
1=W/LOCATING PEG
5. PACKING
R=TAPE&REEL

詮盛企業股份有限公司 CHIENT SHERN ENTERPRISE CO.,LTD.	TITLE	SIM CARD CONN WITH COVER	GENERAL TOLERANCE	DRAWN	許建華	DATE	2005.11.02		
	PART NO.	SIM40-06SA0R	DIM: X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	CHECK		DATE			
	DWG.NO.	SIM40-06SA0R		APPROVE		DATE			
				SCALE	1:1	UNIT	mm	REV.	01